

# TAILOR-MADE STAINS INTERMIX

*A water-based match by Renner Wood Coatings*

Tailor-made stains intermix is the ultimate proposal of the most popular stain colors in the market. The choice of 12 base stains gave birth to an endless number of possible results. Renner Wood Coatings selected 127 stain colors for interior surfaces to facilitate the in-house color matching.

## Tailor-made stains intermix contains

# 12

chips colored  
with base stains

# 127

two-sided chips colored  
with mix of stains



The formulation of every color is water-based, but it imitates the finish of oil-based products thanks to a combination of dyes and pigments. Every stain in this box is unique and inspired by an Italian district.



Every chip has a label containing the reference number and formulation. You can get more details and watch the video tutorial by scanning this QR code.

# TAILOR-MADE STAINS INTERMIX

**AESTHETICS**  
design talks

## BEST FOR

New interior wood surfaces including cabinets, trim, doors, and furniture.

## APPLICATION GUIDELINES

65-75°F with 40-60% humidity represents optimal application conditions. Variations in application and atmospheric conditions can influence drying times and coverage. If the wood is in warm or drier conditions and you desire more open time, please use universal extender AY-M450. Prior to application, ensure surfaces are free from contaminants and dust. Variations in timbers, preparation procedures, and application methods can significantly impact color outcomes. Always conduct a color test before proceeding with staining your project.

## SURFACE PREPARATION

Apply only to new wood or completely stripped old wood. Sand all wood substrates using 150 grit not exceeding 220 grit. Wood must be clean and free of all contaminants or penetration will be compromised.

## APPLICATION ADVICE

Apply the product by wipe, brush, or spray. Wipe off excess for desired effect. Chiaro clear converter can also be utilized as a pre-stain conditioner allowing one to achieve a more uniform look.

## SYSTEM RECOMMENDATIONS

Complete the finishing process with Renner clear products (water-based, acryl, PU or UV coatings) following manufactures suggested application.

## FORCE DRYING

Allow the product to flash off for 10 minutes at room temperature. Heat the surface to °105F by means of IR lamps or oven. Allow it to cool before overcoat. Wait at least 30 minutes between coats.

## GENERAL REMARKS

- Mix very well before use.
- Store the product at temperatures between °50F and °80F, not under direct sun light.
- Shelf life is 12 months.
- Coating leftovers (washing waters, waters from spray booths, used coatings) must be disposed of according to local regulations. Never dispose residues directly into drains.
- Application tools must be cleaned with water after use. If dry films must be removed, use AY-M460, let it work overnight, then rinse with water.

## COLORS AVAILABLE

12 base stains and Chiaro clear converter



BIANCO



TERRA



EMMA



FUOCO



ROSSO



LAVA



VINO



BAITA



PIETRA



CENERE



BUJO



NERO



**Storage**  
50-80°F



**Painting**  
@65-75°F  
with 40-60% humidity



**Thin**  
Water or AY-M450 (extender)  
@max 10%



**Application**  
Brush\* / Roller\* / Pad  
applicator\* / Spray  
\*Use synthetic fiber or foam



**Coverage**  
Up to 650 ft<sup>2</sup>/Gal



**Drying time**  
30 min to touch  
1 h to re-coat



**Sizes Available**  
Gallons  
Pails



**Availability**  
Every color



651 Michael Wylie Drive - Charlotte  
Zip Code 28217 - North Carolina  
T. +1 704 527 9261  
renneritalia.com

Please note that the information and recommendations provided in this document are based on data available at the time of publication and do not serve as a safety data sheet. For complete safety and product data, refer to customer service.